



NHJ600 (D) Series Helium Mass Spectrometer Leak Detector

Introduction

NHJ600 (D) Series Helium Mass Spectrometer Leak Detector is a fully automatic portable helium mass spectrum leak detector, small volume, suitable for precision, fast and portable vacuum industry and research institutes.

Using helium mass spectrometry and inverse diffusion principle, using 180° inhomogeneous magnetic field and automatic control technology. Automatic helium peak scanning, automatic calibration and automatic range switching are realized.

It has the characteristics of portable, fast start, fast operation, high sensitivity, accurate and rapid.

Performance characteristics

Stripping metal button, one-click automatic emptying.

Hand-held remote control unit, up to 150 meters remote detection.

Ram wifi connection, NOY tech app, remote control.

Automatic zero-adjusting, automatic range switching.

The custom software of the leak detector can be compiled according to the customer's request.



Technical Parameters

Min. Detectable Leak Rate of Vacuum Mode	3×10^{-13} Pa·m ³ /s
Vacuum leakage rate display range	$1 \times 10^{-2} \sim 1 \times 10^{-13}$ Pa·m ³ /s
Min. Detectable Leak Rate of Sniffer Mode	5×10^{-9} Pa·m ³ /s
Range of Leakage Rate of Sniffer	$(1 \times 10^{-2} \sim 1 \times 10^{-9})$ Pa·m ³ /s (zero)
Helium Pumping Speed	2.5 L/s
Detectable Gas	⁴ He, ³ He, H ₂
Backing Pump Speed	2.5 m ³ /h
* Dry Backing Pump Speed (optional)	3 m ³ /h
Start-up Time	≤90 s
Response Time	≤0.5 s
Inlet Pressure	≤2000 Pa
Mainframe Power/ Voltage	(200~240) V 50Hz
Work Environment	Temperature (5~40)
Language	Chinese / English
Dimensions	(620x370x480)mm
Weight	47 kg
Display Units	Pa·m ³ /s, mbar·l/s, atm·cc/s, Torr·l/s, ppm

Configuration table

Vacuum pump	Genuine Import
Molecular pump	Genuine Import
Vacuum valve	Original imported leak detector, specially customized
Dry Backing Pump	<input type="radio"/>
Display screen	<input checked="" type="radio"/>
WIFI	<input type="radio"/>
Remote controller	<input type="radio"/>
Sniffer	<input type="radio"/>
Big leak detection	<input checked="" type="radio"/>
Large leakage protection	<input checked="" type="radio"/>
External leak	<input checked="" type="radio"/>
Built-in leak	<input type="radio"/>
Data saving	<input checked="" type="radio"/>
Auto-zero	<input checked="" type="radio"/>
Display interface	Curve chart, histogram, numerical display
I/O interfaces	RRS232, RS485, USB External control input/output, analog output interface

Standard Configuration Optional